




SPF

We switch on the world safely

Aras



Specifications

Gear Box: Aluminium Spinning
Reflector: Injection Polycarbonate
 Polycarbonate lid is optional

Fields Of Application

Offices
 Sport centers
 Stores
 Shopping centers
 Supermarkets

System and Product Certificates



120/230V 50/60 Hz



Code No	Power W	Lamp Type	Igniter	Luminous Flux Lm	Current A	Dimensions(mm) axbxcxØ	Weight Kg	Volume m ³	Base
5213-401	160W	HWL 160	-	3100	0,80	215x405x120x325	1,80	0,045	E-27
5213-402	70W	HQI 70	70-400	5500	1,00	215x405x120x325	3,20	0,045	G-12
5213-410	50W	HQL 50	-	1800	0,60	215x405x120x325	2,50	0,045	E-27
5213-411	80W	HQL 80	-	3800	0,80	215x405x120x325	2,80	0,045	E-27
5213-412	125W	HQL 125	-	6300	1,15	215x405x120x325	3,00	0,045	E-27
5213-422	250W	HWL 250	-	5600	1,20	300x555x135x412	2,00	0,098	E-40
5213-423	70W	HQI 70	70-400	5500	1,00	300x555x135x412	3,50	0,098	G-12
5213-424	150W	HQI 150	70-400	12000	1,80	300x555x135x412	4,10	0,098	G-12
5213-426	250W	HQI 250	70-400	19000	3,00	300x555x135x412	4,50	0,098	E-40
5213-429	250W	HQI 250	-	13000	2,15	300x555x135x412	4,00	0,098	E-40



Email: sales@spfsa.net